



PP Pleated Filters

Product Specification: The Pleated Filter Cartridges are used for low flow OEM equipment, recreational vehicles, food service equipment, reverse osmosis systems, Kidney dialysis equipment, humidifying systems as well as applications with pressures of 6 kg/cm2 and with temperature up to 70°C. The Pleated Filter Cartridges are ideal for flow rating and piping configurations.

Tested For	Hydrostatic leak Burst pressure	
	Sealing	Perfect pressure relieve valve
	Top seated Buna-N 'O' ring	Rugged polypropylene used
Features	BSP thread closure	Colors
	Jumbo Polypropylene Filter housings	White/White
	-1" or 1.5" BSP	Blue/White
	1/2",3/4" and 1" BSP connections-Caps	Blue/Black
	Greater cartridge capacity	White/Blue
	Excellent chemical resistance	

Specifications:

Standard Sizes: 10", 20", 30", 40"

Micron Rating: 1 to 25 Outside Diameter: 64 mm Inner Diameter: 28 mm Applications:

Gasoline Alcohols

Photographic solutions

Food & Beverages: Bottled water,

Flavors, Polishing Lines

Pharmaceuticals: Base product clarifications

Membrane prefilter

Water Treatment: Membrane Protection,

Resin Trap

Rave Filtech Pvt Ltd. 104, 204 First Floor, C-15, Acharya Niketan, Mayur Vihar Phase - 1 Delhi 110091

- + 91 9310505528, +91 9811102134, +91 9811224267
- www.ravefiltech.com
 - ravefpl@yahoo.com, ravefpl@gmail.com